

RSP Ruck Sanitärprodukte GmbH | Kirchstraße 1 | 83126 Flintsbach am Inn | Germany

To our customer

RSP Ruck Sanitärprodukte GmbH
Kirchstraße 1
83126 Flintsbach am Inn
Germany
Phone: +49 (0) 80 34 / 70 82-0
Fax: +49 (0) 80 34 / 70 82-22
info@rsp-rohre.de
www.rsp-rohre.de

Geschäftsführer
Robert Ruck
Amtsgericht Traunstein HRB 15744
USt-IdNr.: DE813975261
Steuer-Nr.: 156/136/80583

Bankverbindung
Sparkasse Rosenheim-Bad Aibling
BLZ 711 500 00
Konto-Nr. 59972
BIC/SWIFT: BYLADEM1ROS
IBAN: DE53 7115 0000 0000 0599 72

Declaration of Performance in accordance with annexe III Regulation (EU) No 305/2011

No.: SML005

- 1.) Unique identification code of the product type:
SML pipe system made of cast iron according to EN877
- 2.) Identification of building product:
RSP-SML pipes and fittings made of cast iron (see product name)
- 3.) Intended use of the construction:
Drainage of waste water or rain water from buildings
- 4.) Name and contact address:
**RSP Ruck Sanitärprodukte GmbH
Kirchstraße 1
D-83126 Flintsbach**
- 5.) Where applicable, authorised representative
Not applicable
- 6.) System of assessment:
**Reaction to fire of the pipe system (System 3), all other properties
(System 4)**
- 7.) Details:
**The approval of reaction to fire as per system 3 was carried out by the notified
agency MFPA Leipzig, NB-Nr. 0800 and a classification report was released.**
- 8.) Product with a European Technical Assessment:
Not applicable

9.) Declared performance:

Essential characteristics	EN 877:2010-01	Performance
Reaction to fire	4.1.3 Reaction to fire, 5.7.3 External coatings and annex H – product group - cast iron - product group system	class A1 class A2-s1,d0
Internal pressure strength	4.7.5 Water tightness	pass
Dimension tolerances	4.2.2 External diameter 4.2.3 Wall thickness 4.2.5 Ovality	pass pass pass
Impact resistance	4.5.2 Mechanical properties	pass
Tightness Air and Water	4.7.5 Water tightness 4.7.6 Air tightness	pass pass
Durability aspects 1. Pipes 2. Fittings	4.6.3 External coatings	1. Epoxy - pass 2. Epoxy - pass
Durability aspects 1. Pipes 2. Fittings	4.6.2 Internal coatings	1. Epoxy - pass 2. Epoxy - pass Resistant to salty spray \geq 1500 h

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer



Flintsbach, 04.04.2019

Robert Ruck (Manager)